



# White Knight

## Clear Sealer Fact Sheet

---

White Knight Clear Sealer is a non yellowing solvent-based acrylic sealer designed to rejuvenate old, weathered, plain and in particular stamped and stencilled concrete surfaces around the home. White Knight Clear Sealer penetrates the concrete to seal and protect. Its unique formulation gives a tough surface layer, which resists extreme Australian weather conditions (sun, rain, cold) as well as dirt, grease and oil. It also helps prevent the growth of mould, mildew, etc. Its strong adhesive properties will help seal exposed aggregate and pebblecrete while strengthening concrete surfaces against eroding and dusting. White Knight Clear Sealer contains a unique additive, which improves slip resistance of the coating when the surface is wet.

Note: White Knight Clear Sealer is not recommended for use on areas around pools, quarry tiles, slate, clay pavers, cement pavers or timber.

### Preparation

The surface must be thoroughly cleaned, dry and free from dust, dirt, grease, oil, efflorescence (white salts), moss, mould and other contaminants. Remove all loose and flaking material. Repair and fill all cracks and damaged areas with an appropriate exterior cement filler. Allow new concrete to cure for 28 days before coating. Wet surfaces should be allowed 5 days of fine weather to ensure they are properly dry.

Here are some important hints to assist you in preparing the surface:

Oil and grease. Degreaser, high-pressure water cleaning; cat litter; warm water and detergent.

Mould, fungus, lichen, moss. High pressure water cleaning; household bleach.

Smooth trowelled concrete. Etch to ensure satisfactory adhesion of coating. See White Knight Concrete Etcher for details.

Removal of White Salts. Thoroughly wet down surface. Treat area affected with White Knight Concrete Etcher, followed by a thorough fresh water rinse and allow to dry. See White Knight Concrete Etcher for details

Allow to dry before painting. After rain, etching or washing, the concrete must be left for a minimum of 5 dry days before painting. White Knight Clear Sealer will not stick to even slightly damp surfaces.

### Application Details

The unique anti slip ingredient may float to the surface on storage. **DO NOT REMOVE.** Stir thoroughly with a broad, flat stirrer in a circular lifting motion before use. Stir at regular intervals during application. Thin the first coat 20-30% with White Knight Rust Guard Solvent. Apply 2 coats. Do not thin the second coat. Apply using a brush or roller with a solvent resistant cover. Use an extension handle for ease of application. Do not use when the air or surface temperature is below 10°C or above 30°C or in damp conditions.

PROVIDE ADEQUATE VENTILATION DURING USE AND WHILE DRYING

### Drying Times

Touch dry in 1 hour. Recoat after 2 hours. Drying times may be extended in low temperature and high humidity.

On driveways and garage floors, allow 72 hours before driving vehicles on the coated surface.

### Coverage

Up to 8 square metres per litre, depending on nature of the surface.

### Clean Up

Clean brushes and equipment with White Knight Rust Guard Solvent.

To remove oil or grease from White Knight Clear Sealer coated surfaces, use

a suitable concrete degreaser. Do NOT use thinners as this will remove the clear protective layer of White Knight Clear Sealer. Reapply White Knight Clear Sealer as required. For most other spillages, simply clean with detergent and wash with fresh water.

Do not pour unwanted paint down the drain. Keep unwanted paint in sealed containers for disposal via special chemical waste collections. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs.

Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

### Health and Safety

Refer to Material Safety Data Sheet available by request on 131 686.

---

### Got more questions? Need help? Want a brochure? Any comments or suggestions on the site?

If you have any comments or questions on the White Knight range or want more information we are here to help.

### Contact Us

#### Customer Care Advisers

Phone 131 686

Fax 1800 676 756

Opening Hours: Mon-Fri 8am to 7pm EST, Sat/Sun 9am to 4pm EST

Email [info@whiteknightpaints.com.au](mailto:info@whiteknightpaints.com.au)