



# White Knight

## Rust Guard Super Primer Fact Sheet

---

White Knight Super Primer is a high quality, quick drying primer especially formulated as an anti-corrosive primer and undercoat for ferrous metals. The tough finish gives excellent adhesion making the ideal preparation for top coating.

### Suitable Surfaces

Super Primer is ideal for use on ferrous metals plus timber and masonry surfaces and is suitable under all most top coats.

### Preparation

The surface must be thoroughly cleaned, dry and free from grease, oil, dirt, salt rust scale and other contaminants. All loose material must be removed by wire brushing or mechanical sander until a firm metal base is established. BEFORE SPRAYING Cover all necessary areas to protect from overspray. It is essential to shake the can for at least one minute after mixing ball rattles to ensure product uniformity. Shake can occasionally during use. Do not use when the air or surface temperature is below 15°C or above 30°C or in excessive humidity.

### Application Details

Spray outside or in a well ventilated area away from fire and heaters. Test spray first on a small inconspicuous area to ensure surface compatibility and finish suitability. Hold the can upright approximately 15-20 cm from the surface. Press button firmly. Spray with a smooth sweeping motion. Apply a pre-wetting mist coat followed by a full even coat. Overlap each spray pass. Repeat if necessary. To prevent paint sagging, avoid spraying too close to the surface or spraying too heavy a coat. After Spraying: To clean the nozzle after use and prevent blocking, turn the can upside down and press button until only gas escapes.

### Coverage

Up to 1 to 1.5 square metres per unit depending on the nature of the surface and the amount of overspray.

### Drying Times

Touch dry: 10 minutes. Re-Coat: After 1 hour. Drying times will be slower in cold or humid conditions, in the absence of ventilation or where heavy film builds are applied

### Clean Up

Overspray can be removed while still wet with mineral turps.

### Pack Sizes

300g spray

### Health and Safety

Refer to Material Safety Data Sheet available by request on 131 686.

### HANDY HINT

Available in three colours to compliment a wide range of finishing colours. For example, if you were painting a yellow topcoat the white primer would be suitable but if you are painting a red topcoat the red primer would be recommended.

Can be applied to a wide range of surfaces.

To remove a child proof cap insert a screwdriver in the cap and lever it up

The horizontal setting is used when spraying up and down and press button until only gas escapes.

To clean nozzle after use and prevent blocking turn the can upside down and press button until only gas escapes.

---

## Got more questions? Need help? Want a brochure? Any comments or suggestions on the site?

If you have any comments or questions on the White Knight range or want more information we are here to help.

### Contact Us

#### Customer Care Advisers

Phone 131 686

Fax 1800 676 756

Opening Hours: Mon-Fri 8am to 7pm EST, Sat/Sun 9am to 4pm EST

Email [info@whiteknightpaints.com.au](mailto:info@whiteknightpaints.com.au)